



MODEL	: W4 Diesel
INTENDED USE	: High Pressure Compressed Air / Breathing
Air	
FILTER SYSTEM	: Filter + P61 Purification
MAX. WORKING PRESSURE	: 6000 psi (415 Bar)
NUMBER OF STAGES	: 4
NUMBER OF CYLINDERS	: 3
LUBRICATION SYSTEM	: Splash Lubrication
NUMBER OF FILLING HOSES	: 4
LUBRICANT CAPACITY	: 4 L (1.06 US gal.)
LUBRICANT	: Anderol 755
POWER TRANSMISSION	: Belt-Pulley
WORKING TEMPRANGE	: 32...122°F (0...+50 °C)
INTERNATIONAL WARRANTY	: 2 Years

CFM	Power	RPM	Dimensions (in.)	Weight (lbs)
22	Diesel	830	33x66x57	1500
31	Diesel	755	37x50x68	1984



STANDARD FEATURES

P61 Purifier (Stainless Steel) with Refillable Purifier Element (Stainless Steel)
High Pressure Particle and Oil Separator (Stainless Steel)
2nd, 3rd & 4th Stage Water Condensate and Oil Separator (Stainless Steel)
Intercoolers (Stainless Steel)
Aftercooler (Stainless Steel)
Priority Valve (Pressure Maintaining Valve)
Check Valve
Safety Valve at Each Stage
Oil Level Glass
Oil Level Switch
Electrostatically Painted Chassis
Vibration Mounts
Electric Start
Auto Shutoff
Auto Condensate Drain
Pressure Switch
Control Panel: On/Off Button, Hourmeter, Stage Pressure Gauges & Purifier Gauge
Filling Panel with 4 Filling Hose (Yokes, Filling Valves, Pressure Gauges, DIN Adapters)
Air Quality complies with EN 12021, Grade E and Grade D

OPTIONAL FEATURES

PLC Touchscreen Control System
Oxygen, Carbon Monoxide, Moisture Sensors
Remote Monitoring and Control
Dual Pressure Systems 225-415 Bar / 3260-6000 Psi
Stainless Canopy
Disposable Filter Cartridge
Extra Filling Hoses