



MODEL	: 702 Chassis
INTENDED USE	: Medium Pressure Compressed Air
INLET PRESSURE	: Atmospheric
MAX. WORKING PRESSURE	: 580 psi (40 Bar)
NUMBER OF STAGES	: 2
NUMBER OF CYLINDERS	: 3
LUBRICATION SYSTEM	: Splash Lubrication
LUBRICANT CAPACITY	: 3 L (0.79 US gal.)
LUBRICANT	: Anderol 755 / Mobil Rarus 427
POWER TRANSMISSION	: Belt-Pulley
WORKING TEMPRANGE	: 32...122°F (0...+50 °C)
DIMENSIONS	: 30x51x34 in.
INTERNATIONAL WARRANTY	: 2 Years

Motor Power	Weight (lbs)	CFM (L/Min)	RPM
15	716	26.5 (750)	830
20	738	35.3 (1000)	1200
25	760	42.4 (1200)	1450



## STANDARD FEATURES

Intercoolers  
Aftercooler  
Safety Valve at Each Stage  
Check Valve  
Pressure Switch for Auto Start / Stop  
Water Separator  
Drain Solenoid  
Stage and Discharge Pressure Gauges  
Oil Level Sight Gauge  
Electrostatically Painted Chassis  
Vibration Mounts and Base  
Thermal Overload Protection for Electric Motor  
Wall Mounted Control & Electric Panel: YΔ Starter, Main Switch, On/Off Buttons, Hourmeter, Emergency Push Buttons, Control Leds

## OPTIONAL

Low Oil Level Switch  
Control Panel: Main Switch, On / Off Buttons, Hourmeter, Test, Reset and Emergency Pushbuttons, Control Leds  
Electric Panel: YΔ Starter