



## MEDIUM PRESSURE AIR COMPRESSOR

<b>MODEL</b>	: 526	
<b>INTENDED USE</b>	: Compressed Air	
<b>FILTER SYSTEM</b>	: Optional	
<b>WORKING PRESSURE</b>	: 580 psi (40 Bar)	
<b>FAD, CAPACITY</b>	: 1000 lt/min, 35.3 CFM	1200 lt/min, 42 CFM
<b>MOTOR POWER</b>	: 20 hp	25 hp
<b>COMPRESSOR SPEED</b>	: 640 rpm	750 rpm
<b>NUMBER OF STAGE</b>	: 2	
<b>NUMBER OF CYLINDER</b>	: 3	
<b>LUBRICATION SYSTEM</b>	: Forced Lubrication	
<b>POWER TRANSMISSION</b>	: Belt-Pulley	
<b>OPERATING TEMP RANGE</b>	: 32...122 F (0...+50 C)	
<b>DIMENSIONS (WxLxH)</b>	: 30 x 47 x 68 inches	
<b>WEIGHT</b>	: 1411 lbs.	1433 lbs.

### STANDART EQUIPMENT

Inter and After Cooler Pipes (Stainless)
Water and Oil Separator
Safety Valve at Each Stage
Check Valve
Manometers Showing Inlet and Outlet Pressure
Pressure Automatic for Automatic Start/Stop
Discharge Solenoid
Oil Level Switch
Electrostatic Painted Chassis
Oil Level Sight Gauge
Thermal Overload Protection for Electric Motor
Shock Mounts

### OPTIONAL

PLC Touch Screen Control System
Stainless Chassis