



MODEL : W4 - Water Cooled
INTENDED USE : High Pressure Compressed Air / Breathing Air
FILTER SYSTEM : Filter + P61 Purification
MAX. WORKING PRESSURE : 6000 psi (415 Bar)
NUMBER OF STAGES : 4
NUMBER OF CYLINDERS : 3
LUBRICATION SYSTEM : Splash Lubrication
LUBRICANT CAPACITY : 4 L (1.06 US gal.)
LUBRICANT : Anderol 755
POWER TRANSMISSION : Belt-Pulley
WORKING TEMPRANGE : 32...122°F (0...+50 °C)
INTERNATIONAL WARRANTY : 2 Years

CFM	Engine	RPM	Dimensions (in.)	Weight (lbs)
22	Diesel	830	33x66x57	1500
31	Diesel	755	37x50x68	1600



STANDARD FEATURES

1st, 2nd, 3rd & 4th Stage Water Condensate and Oil Separator
Fresh / Sea Water Cooling System
Intercooler Heat Exchangers (Stainless Steel)
Cathodic Protection
Check Valve
Safety Valves at Each Stage
Electrostatically Painted Silent Canopy
Auto Condensate Drain
Automatic Start / Stop
Pressure Switch
Water Pressure Switch
Oil Pump
Oil Pressure Switch
Oil Dipstick
Oil Filters
Shock Mounts
Thermal Overload Protection for Electric Motor
Stage Pressure Gauges, Oil Pressure Gauge, Cooling Water Pressure Gauge

OPTIONAL FEATURES

Diesel / Gas / Electric engines available