



MODEL : 526 Canopy Booster
INTENDED USE : Compressed Air / Gas
INLET PRESSURE : 116 psi (8 Bar)
WORKING PRESSURE : 580 psi (40 Bar)
NUMBER OF STAGE : 1
NUMBER OF CYLINDER : 3
LUBRICATION SYSTEM : Splash Lubrication
LUBRICANT CAPACITY : 4 L (1.05 US gal.)
LUBRICANT : Anderol 755 / Mobil Rarus 427
POWER TRANSMISSION : Belt-Pulley
WORKING TEMP. RANGE : 32... 122F (0... +50 C)
DIMENSIONS : 30x47x68 in.
INTERNATIONAL WARRANTY : 2 Years

CFM (L/min)	RPM	Motor Power (hp)	Weight (lbs)
134.20 (3800)	570	20	1370
176.57 (5000)	750	25	1390
211.89 (6000)	840	30	1410



STANDARD FEATURES

Intercooler and Aftercooler (Stainless Steel)
Priority Valve (Pressure Maintaining Valve)
Check Valve (Non-Return Valve)
Safety Valve for Each Stage
Oil Level Switch
Oil Level Sight Gauge
Inlet and Discharge Manifolds
Inlet and Discharge Pressure Gauges
Pressure Switch Gauge for Automatic Start / Stop
Automatic Drain
Water Separator
Thermal Overload Protection for Electric Motor
Drain Solenoid
Electrostatically Painted Silent Canopy
Vibration Mounts and Subbase isolated from Canopy for Smoothest Operation
Control & Electric Panel
Twin Top Forced Ventilation Fans for Better Cooling

OPTIONAL FEATURES

PLC Touch Screen Control System
Stainless Canopy